

## SPECIFICATIONS

**Model**

FO

**Weight**

48 lbs

**Dimensions**

Height 13.2"

Depth 27"

Width 27"

\*Intended for indoor use only



## DETAILS

**Finishes**

See Design Guide for finish options.

\*Due to differences in monitors, printers and materials, actual product colors may vary. Color chips are available for more accurate depiction of color.

**Options**

Factory Ballasting (50 lbs)

\*Ballastable up to 100 pounds of dry sand or gravel. On site ballast materials not supplied by Norix.

**Assembly**

None required

**Installation**

Required for ganging plates and ballast.

Ballast weighting required to validate warranty. Recommend 100 pounds of dry sand or gravel. On site ballast materials not supplied by Norix.

**Warranty**

10 year limited replacement warranty.

**Fabrication & Material**

**Top:** Decorative high pressure laminate is bonded to a core of 45 lb density particle board with embedded T-nuts for securing top to base. Polyurethane edge is radiused for safety and pressure fused to the top, rendering it firmly attached and highly sanitary. 1<sup>3</sup>/<sub>4</sub>" thick edge profile.

**Base:** Specially formulated, high-impact polyethylene with ultraviolet light stabilizers (to reduce fading). Chemically resistant to blood, vinegar, urine, feces, salt solution and chlorine solution. Premium TruColor™ material is fully compounded for superior color consistency and durability. Molded-in steel threaded inserts for optional ganging side-to-side. Push in cap seals access port for sand or gravel ballast capability. Anti-ligature design with no internal openings. Made in the U.S.A.

**Maintenance**

**Top:** For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product.

**Base:** For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product. This product is bleach/water solution cleanable and suitable for use with hospital-grade disinfectants (such as Virex®, Wexcide® or Oxivir Five 16®) per manufacturers' instructions.

## TESTING

**Performance Test Standards**

Tested to 1,000 lb static load

**Environmental Test Standards**

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG. Plastic is Recyclable #7
- Compliant with Healthier Hospitals guidelines

**Flammability Test Standards**

Compliant with the following flammability standards:

- State of California, Technical Bulletin No. 133, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- UL1056 Fire Test of Upholstered Furniture
- ASTM E1537 Test Method for Fire Testing of Real Scale Upholstered Furniture Items
- NFPA 261 Cigarette Ignition Resistance of Upholstered Furniture
- UL94 HB Test for Flammability of Plastic Materials